

## MATERIAL SAFETY DATA SHEET

The following form is intended to contain all information as required by the standards and regulatory requirements of the United States and may not meet regulatory requirements of other countries.

### Superpack™ **STYLE 104 Bumblebee Packing** ®

This form also covers **Style 104SC, Style 104AF , 102/150 Seal Rope and Style 204**

#### **SECTION I: COMPANY INFORMATION**

Manufactured by:  
New England Braiding Company, Inc.  
Address:  
610 Gold Street  
Manchester, New Hampshire 03103  
Revised by: L. Finnegan

Emergency Telephone  
603-669-1987  
Telephone # for Information  
603-669-1987  
Date Revised: 06/06/07  
Reviewed--no changes

#### **SECTION II: HAZARDOUS INGREDIENTS / IDENTITY INFORMATION**

**Hazardous Components:** None anticipated under intended conditions of use.

**Note:** This product is essentially inert in all intended uses up to 500°F (260°C); **however**, it should **NOT** be used in contact with tobacco or tobacco products and hands should be washed after handling this product prior to smoking. See Sec. V.

**Identity:** Referenced packing is manufactured from a combination of aramid yarn and TFE/graphite composite yarn with a proprietary break-in lubricant. Style 104SC incorporates Silicone cord stock in its construction. Style 104AF incorporates AFLAS® cord stock.

#### **SECTION III: PHYSICAL/CHEMICAL CHARACTERISTICS**

**Boiling Point:** N/A

**Vapor Pressure (mm Hg.):** N/A

**Vapor Density (air=1):** N/A

**Solubility in Water:** Insoluble

**Appearance:** Style 104 black braided solid with four yellow, diagonally opposed corners, Style 204 has 2 diagonally opposed corners. Style 104SC includes red cord stock fill and Style 104AF includes black cord stock fill. Style 102/150 is black braided solid with yellow internal fill in the center. The fill is only visible at the cut ends.

**Specific Gravity (H<sub>2</sub>O=1):** 1.3

**Melting Point:** Does not melt

**Evaporation. Rate:** N/A

**Odor:** No odor

#### **SECTION IV: FIRE AND EXPLOSION HAZARD DATA**

**Flash Point (Open Cup):** N/A

**Flammable Limits:** N/A

**Extinguishing Media:** CO<sub>2</sub>, dry chemical, foam, Halon, water

**Special Fire-Fighting Procedures:** Use self-contained breathing apparatus (SCBA) to protect against decomposition gasses.

**Unusual Fire & Explosion Hazards:**

Material does not support combustion but thermal decomposition of TFE begins above 550°F (288°C) and may produce toxic gases including but not limited to carbon dioxide, nitrogen oxides and aliphatic hydrocarbons.

---

**MSDS Styles 104, 204, 102/150, 104SC, 104AF**

---

**SECTION V: REACTIVITY DATA**

**Stability:** Stable at normal temperature and storage conditions

**Conditions to Avoid:** Do NOT incinerate.

Polymer—Overheating (>300°C or 572°F) may create thermal decomposition products that could result in irritation of the mucous membranes, eyes, skin, respiratory tract, or polymer fume fever. Polymer fume fever is a temporary flu-like illness with fever and chills of approximately 24-48 hours duration.

**Hazardous Decomposition or Byproducts:** Trace amounts only of hydrogen fluoride gas and perfluorocarbon olefins may evolve over 752°F (400°C).

**Hazardous Polymerization:** Will not occur

**SECTION VI: HEALTH HAZARD DATA**

**Health Hazards (Acute & Chronic):** NONE - materials are essentially inert under normal conditions, however, smoking after handling may create conditions for "polymer fume fever". See Section V. Always wash hands after smoking.

**Medical conditions generally aggravated by exposure:** None known

**Emergency & First Aid Procedures:** In a fire, treat exposure to fumes for hydrogen fluoride exposure if irritation occurs. For "Polymer Fume Fever", treat as required by symptom.

**SECTION VII: PRECAUTIONS FOR SAFE HANDLING**

**Steps to be Taken in Case Material is Released or Spilled:** N/A

**Waste Disposal Method:** Do NOT incinerate. Not biodegradable. Dispose of used material in accordance with Federal, State, and Local regulation. Check service material was used in to determine if used material may have absorbed hazardous materials from service and thus require special handling.

**Precautions to be Taken in Handling & Storing:** Wash hands after handling, especially prior to smoking.

**Other Precautions:** Do NOT smoke or handle smoking materials while handling this product. Wash hands first. Thermal decomposition of polymer on smoking materials may cause "Polymer Fume Fever". See Section V above.

**SECTION VIII: CONTROL MEASURES**

**Eye Protection:** Wear safety glasses or coverall goggles when cutting or mechanically working this product, or when airborne dust may be present.

**Respiratory Protection:** Respiratory protection is not normally required under anticipated working conditions of use. Wear NIOSH/MISHA approved respiratory protection.

**In case of fire,** use self-contained breathing apparatus to prevent exposure to products of thermal breakdown. Cover exposed skin areas to prevent exposure to possible hydrogen fluoride gas. Wear NIOSH/MISHA approved respiratory protection that complies with OSHA Standard 29 CFR 1910.134

**Ventilation:** Local exhaust should be filtered and conditioned to eliminate respirable fibers, dust and fumes.

**Other Protective Clothing or Equipment:** As required for personnel during installation or removal by local plant practice. Consider personnel exposure to service fluid that may be absorbed by this material during use.

**Work/Hygienic Practices:** Wash hands after handling. **DO NOT** smoke when handling. Wash hands before smoking. See Section V.

---

**MSDS Styles 104, 204, 102/150, 104SC, 104AF**

---

**SECTION IX: FIRST AID MEASURES**

**Eye Contact:** Flush eyes with plenty of water. Seek medical attention.

**Ingestion:** Not a plausible route.

**Inhalation:** If large amounts of fumes, dust or fibers are inhaled remove to fresh air. If persistent cough or other systems develop, seek medical attention.

**THE INTENDED USE OF THIS PRODUCT MEETS THE DEFINITION OF AN ARTICLE UNDER 29 CFR 1910.1200.**

---

**The above data describes exclusively the safety requirements of the product and is based on our current base of knowledge. It does not relate to use in combination with other materials or in any process. No guarantee is expressed or implied.**

MSDS104 204 102/150.DOC  
F:\DATA\WORD\Packing MSDS104 204 102/150 104SC 104AF.DOC